

GREEN XLR 65 (R-1W)

Tire Size	LI/SS	Type	Rim		Unloaded Inflated Dimension± 2%				SLR		RC ± 2.5%		RCI	SRI	Maximum Load Capacity (lbs)								Maximum Load Capacity (kgs)								Tire weight	Tire weight	Tread Depth	Tread Depth	Product Code			
					S.W.		O.D.																															
			Rec.	Alt.	mm	inch	mm	inch	mm	inch	mm	inch			mm	inch																						
24"	440/65R24	135 D / 138 A8	TL	W 14 L	W13,W15	441	17.4	1182	46.5	538	21.2	3546	139.6	575	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	kgs	lbs	mm	32nds	PAR1408	
															40	2315	2700	3030	3375	3705	3990	4430	4805	65	1050	1225	1375	1530	1680	1810	2010	2180						
															30	2425	2835	3185	3540	3890	4200	4655	5050	50	1100	1285	1445	1605	1765	1905	2110	2290						
															25	2505	2920	3285	3650	4015	4320	4795	5205	40	1135	1325	1490	1655	1820	1960	2175	2360						
															20	2655	3110	3495	3880	4265	4595	5095	5535	30	1205	1410	1585	1760	1935	2085	2310	2510						
															5 LT	3100	3615	4070	4520	4970	5360	5940	6450	10 LT	1410	1640	1845	2050	2255	2430	2695	2925						
															5 HT	2655	3110	3495	3880	4265	4595	5095	5535	10 HT	1205	1410	1585	1760	1935	2085	2310	2510						
															mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4						
															40	2645	3085	3475	3860	4245	4575	5070	5515	65	1200	1400	1575	1750	1925	2075	2300	2500						
															30	2780	3240	3650	4055	4465	4805	5325	5790	50	1260	1470	1655	1840	2025	2180	2415	2625						
25	2890	3375	3795	4210	4630	4995	5535	6010	40	1310	1530	1720	1910	2100	2265	2510	2725																					
20	3045	3550	4000	4445	4885	5270	5830	6340	30	1380	1610	1815	2015	2215	2390	2645	2875																					
5 LT	3550	4145	4665	5170	5690	6140	6800	7385	10 LT	1610	1880	2115	2345	2580	2785	3085	3350																					
5 HT	3045	3550	4002	4443	4884	5270	5832	6339	10 HT	1380	1610	1815	2015	2215	2390	2645	2875																					
28"	440/65R28	138 D / 141 A8	TL	W 14 L	W13	441	17.4	1283	50.5	590	23.2	3878	152.7	39	625	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	kgs	lbs	mm	32nds	PAR1413
																40	2505	2920	3285	3650	4015	4320	4795	5205	65	1135	1325	1490	1655	1820	1960	2175	2360					
																30	2635	3065	3450	3835	4210	4540	5040	5470	50	1195	1390	1565	1740	1910	2060	2285	2480					
																25	2735	3185	3585	3980	4375	4720	5225	5680	40	1240	1445	1625	1805	1985	2140	2370	2575					
																20	2880	3365	3780	4200	4620	4970	5515	5985	30	1305	1525	1715	1905	2095	2255	2500	2715					
																5 LT	3350	3915	4400	4895	5380	5800	6430	6980	10 LT	1525	1775	1995	2220	2440	2630	2915	3165					
																5 HT	2880	3365	3780	4200	4620	4970	5515	5985	10 HT	1305	1525	1715	1905	2095	2255	2500	2715					
																mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4					
																40	2810	3275	3680	4090	4510	4850	5380	5845	65	1275	1485	1670	1855	2045	2200	2440	2650					
																30	2955	3440	3870	4300	4730	5105	5655	6140	50	1340	1560	1755	1950	2145	2315	2565	2785					
25	3075	3585	4035	4475	4930	5315	5885	6395	40	1395	1625	1830	2030	2235	2410	2670	2900																					
20	3230	3770	4245	4710	5180	5590	6195	6725	30	1465	1710	1925	2135	2350	2535	2810	3050																					
5 LT	3770	4400	4940	5490	6040	6515	7220	7840	10 LT	1710	1995	2240	2490	2740	2955	3275	3555																					
5 HT	3230	3770	4245	4710	5180	5590	6195	6725	10 HT	1465	1710	1925	2135	2350	2535	2810	3050																					
30"	540/65R28	149 D / 152 A8	TL	W 16 L	W 18 L	530	21	1413	55.6	643	25.3	4253	167.4	41	675	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	kgs	lbs	mm	32nds	PAR1401
																40	3440	4010	4515	5015	5515	5945	6590	7165	65	1560	1820	2050	2275	2505	2700	2990	3250					
																30	3610	4215	4740	5265	5795	6245	6920	7530	50	1640	1910	2150	2390	2630	2830	3140	3415					
																25	3760	4385	4925	5480	6030	6495	7200	7825	40	1705	1990	2235	2485	2735	2945	3265	3550					
																20	3955	4615	5190	5770	6345	6840	7580	8245	30	1795	2095	2355	2615	2880	3100	3440	3740					
																5 LT	4610	5375	6050	6720	7395	7970	8835	9600	10 LT	2095	2440	2745	3050	3355	3615	4005	4355					
																5 HT	3955	4615	5190	5770	6345	6840	7580	8245	10 HT	1795	2095	2355	2615	2880	3100	3440	3740					
																mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4					
																40	3970	4630	5214	5785	6365	6880	7605	8265	65	1800	2100	2365	2625	2890	3115	3450	3750					
																30	4165	4860	5467	6075	6685	7205	7985	8680	50	1890	2205	2480	2755	3030	3270	3625	3940					
25	4365	5095	5730	6365	7000	7550	8365	9095	40	1980	2310	2600	2890	3175	3425	3795	4125																					
20	4565	5325	5985	6655	7320	7890	8745	9505	30	2070	2415	2715	3020	3320	3580	3970	4315																					
5 LT	5375	6205	6978	7755	8530	9195	10190	11080	10 LT	2410	2815	3165	3520	3870	4170	4625	5025																					
5 HT	4565	5325	5985	6655	7320	7890	8745	9505	10 HT	2070	2415	2715	3020	3320	3580	3970	4315																					
34"	540/65R30	150 D / 153 A8	TL	W 16 L	W 18 L	530	20.9	1460	57.5	670	26.4	4403	173.3	700	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	Kg	lbs	MM	32nds	PAR1403	
															40	3545	4135	4655	5170	5685	6130	6795	7385	65	1610	1875	2110	2345	2580	2780	3080	3350						
															30	3720	4345	4885	5430	5970	6435	7135	7755	50	1690	1970	2215	2460	2710	2920	3235	3520						
															25	3860	4505	5070	5635	6195	6680	7405	8045	40	1750	2045	2300	2555	2810	3030	3360	3650						
															20	4075	4755	5350	5945	6540	7050	7815	8495	30	1850	2155	2425	2695	2965	3200	3545	3855						
															5 LT	4750	5540	6235	6930	7620	8215	9105	9895	10 LT	2155	2515	2830	3140	3455	3725	4130	4490						
															5 HT	4075	4755	5350	5945	6540	7050	7815	8495	10 HT	1850	2155	2425	2695	2965	3200	3545	3855						
															mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4						
															40	4365	5095	5735	6370	7010	7550	8370	9095	65	1980	2310	2600	2890	3180	3425	3795	4125						
															30	4595	5360	6030	6690	7365	7940	8800	9560	50	2085	2430	2735	3035	3340	3600	3990	4335						
25	4765	5555	6250	6945	7640	8235	9130	9925	40	2160	2520	2835	3150	3465	3735	4140	4500																					
20	5025	5865	6595	7330	8060	8690	9635	10465	30	2280	2660	2990	3325	3655	3940	4370	4745																					
5 LT	5855	6835	7685	8545	9395	10120	11225	12195	10 LT	2660	3100	3485	3875	4260	4590	5090	5530																					
5 HT	5025	5865	6595	7330	8060	8690	9635	10465	10 HT	2280	2660	2990	3325	3655	3940	4370	4745																					
38"	540/65R38	153 D / 156 A8	TL	W16L	W18L	530	20.9	1667	65.6	760	29.9	5059	199.2	44	800	mph/psi	9	12	15	17	20	23	29	35	kmph/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	kgs	lbs	mm	32nds	PAR1412
																40	3870	4510	5070	5635	6205	6680	7410	8050	65	1755	2045	2300	2555	2815	3030	3360	3650					
																30	4070	4740	5335	5920	6515	7025																

600/65R38	159 D / 162 A8	TL	DW 20 B	W 18 L	611	24.1	1745	68.7	790	31.1	5247	206.6	45	825	5 HT	4455	5195	5845	6485	7135	7695	8520	9260	10 HT	2020	2355	2650	2940	3235	3490	3865	4200													
															mph/psi	9	12	15	17	20	23	29	35	kmpH/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4													
															40	4630	5400	6075	6750	7425	8005	8875	9645	65	2100	2450	2755	3065	3370	3630	4025	4375													
															30	4860	5670	6380	7090	7800	8405	9315	10125	50	2205	2575	2895	3215	3535	3815	4225	4595													
															25	5025	5865	6595	7330	8065	8690	9635	10470	40	2280	2660	2995	3325	3660	3945	4370	4750													
															20	5325	6210	6990	7765	8540	9205	10205	11090	30	2415	2820	3170	3520	3875	4175	4630	5030													
															5LT	6205	7240	8140	9045	9950	10725	11890	12925	10 LT	2820	3285	3695	4105	4515	4865	5395	5865													
															5HT	5325	6210	6990	7765	8540	9205	10205	11090	10 HT	2415	2820	3170	3520	3875	4175	4630	5030													
															mph/psi	9	12	15	17	20	23	29	35	kmpH/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4													
															40	5160	6020	6770	7525	8275	8920	9890	10745	65	2340	2730	3070	3415	3755	4045	4485	4875													
30	5415	6320	7110	7900	8690	9365	10380	11285	50	2455	2865	3225	3585	3940	4250	4710	5120																												
25	5610	6545	7360	8180	8995	9700	10750	11685	40	2545	2970	3340	3710	4080	4400	4875	5300																												
20	5935	6920	7785	8650	9515	10260	11370	12360	30	2690	3140	3530	3925	4315	4655	5160	5605																												
5LT	6915	8065	9075	10080	11090	11955	13250	14400	10 LT	3140	3660	4115	4575	5030	5420	6010	6535																												
5HT	5935	6920	7785	8650	9515	10260	11370	12360	10 HT	2690	3140	3530	3925	4315	4655	5160	5605																												
650/65R38	163 D / 166 A8	TL	DW 20 B	46	645	25.4	1811	71.3	830	32.7	5483	215.9	875	mph/psi	11.6	14.5	17.4	20.3	23.2	34.8	46.4	52.2	kmpH/bar	0.8	1	1.2	1.4	1.6	2.4	3.2	3.6														
														40	6970	7250	7560	7870	8200	8660	11380	12350	65	3160	3290	3430	3570	3720	4380	5160	5600														
														30	7320	7610	7940	8270	8620	10140	11950	12960	50	3320	3450	3600	3750	3910	4600	5420	5880														
														25	7630	7940	8290	8620	8970	10580	12460	13510	40	3460	3600	3760	3910	4070	4800	5650	6130														
														20	8000	8330	8690	9060	9440	11110	13070	14200	30	3630	3780	3940	4110	4280	5040	5930	6440														
														5LT	9260	9660	10050	10470	10910	12850	15120	16420	10 LT	4200	4380	4560	4750	4950	5830	6860	7450														
														5HT	8000	8330	8690	9060	9440	11110	13070	14200	10 HT	3630	3780	3940	4110	4280	5040	5930	6440														
														SL	16030	16690	17390	18100	18870	22200	26170	28400	SL	7270	7570	7890	8210	8560	10070	11870	12880														
														650/65R38	172 D / 175 A8	TL	DW 20 B	46	645	25.4	1811	71.3	830	32.7	5483	215.9	875	mph/psi	12	15	17	20	23	35	46	52	kmpH/bar	0.8	1	1.2	1.4	1.6	2.4	3.2	3.6
																												40	7870	8200	8530	8880	9260	10890	12810	13890	65	3570	3720	3870	4030	4200	4940	5810	6300
30	8270	8620	8950	9330	9720	11440	13450	14590	50	3750	3910	4060	4230															4410	5190	6100	6620														
25	8620	8970	9350	9720	10140	11930	14020	15210	40	3910	4070	4240	4410															4600	5410	6360	6900														
20	9060	9440	9810	10210	10650	12520	14730	15980	30	4110	4280	4450	4630															4830	5680	6680	7250														
5LT	10470	10910	11350	11820	12320	14480	17040	18470	10LT	4750	4950	5150	5360															5590	6570	7730	8380														
5HT	9060	9440	9810	10210	10650	12520	14730	15980	10HT	4110	4280	4450	4630															4830	5680	6680	7250														
SL	18100	18870	19620	20440	21300	25040	29450	31940	SL	8210	8560	8900	9270															9660	11360	13360	14490														
650/65R42	165 D / 168 A8	TL	DW 20 B	46	645	25.4	1913	75.3	864	34.0	5740	226.0	925															mph/psi	9	12	15	17	20	23	29	35	kmpH/bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
																												40	5450	6360	7155	7950	8740	9425	10445	11353	65	2470	2885	3245	3605	3965	4275	4740	5150
														30	5720	6675	7510	8345	9180	9895	10970	11920	50	2595	3030	3245	3785	4165	4490	4975	5410														
														25	5925	6915	7780	8640	9505	10245	11360	12345	40	2690	3135	3530	3920	4310	4650	5150	5600														
														20	6265	7310	8225	9140	10055	10835	12010	13055	30	2845	3315	3730	4145	4560	4915	5450	5925														
														5LT	7305	8520	9585	10650	11715	12630	13995	15215	10 LT	3310	3865	4350	4830	5315	5730	6350	6900														
														5HT	6265	7310	8225	9140	10055	10835	12010	13055	10 HT	2845	3315	3730	4145	4560	4915	5450	5925														

42"